

## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

No. LE\_GI 219\_V03

Unique identification code of the product-type:	GI 219
Intended use/es:	EN 1504-2 Surface protection products – Coating Protection against ingress (1.3) Moisture control (2.2) Physical resistance (5.1) Resistance to chemicals (6.1) Increasing resistivity (8.2)  EN 13813 Synthetic resin screed for internal uses
Manufacturer:	Gremmler Bauchemie GmbH Lise-Meitner-Strasse 5 46569 Hünxe
System/s of AVCP:	EN 1504-2: System 2+ (for uses in buildings and civil engineering works) EN 13813: System 4 (for internal uses)
Harmonised standard:	EN 1504-2:2004 EN 13813:2002
Notified body/ies:	Kiwa Polymer Institut, identification number 1119

Declared performance:

EN 1504-2:

The product is used in surface protection system consisting of components:

Primer: GI 110, GI 115 or GI 118

Coating: GI 130

Sealing: GI 219

Table 1: Performance in system according to EN 1504-2

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Linear shrinkage	NPD	System 2+	EN 1504-2:2004
Compressive strength	NPD		
Coefficient of thermal expansion	NPD		
Abrasion resistance	< 3000 mg		
Cross cut	NPD		
Permeability to CO <sub>2</sub>	s <sub>D</sub> > 50 m		
Water vapour permeability	class III		
Capillary absorption and permeability to water	w < 0.1 kg/(m <sup>2</sup> x h <sup>0,5</sup> )		
Thermal compatibility	NPD		
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Resistance to severe chemical attack	class I		
Crack bridging ability	NPD		
Impact resistance	class I		
Adhesion strength by pull off test	≥ 2.0 (1.5) N/mm <sup>2</sup>		
Reaction to fire	class E		
Skid resistance	NPD		
Artificial weathering	NPD		
Antistatic behaviour	NPD		
Adhesion on wet concrete	NPD		
Release of dangerous substances	NPD		

Table 2: Performance according to EN 13813

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire <sup>1)</sup>	class E <sub>fi</sub>	System 4	EN 13813:2002
Release of corrosive substances	SR		
Water permeability	NPD		
Wear resistance	AR 1		
Bond strength	B 1.5		
Impact resistance	IR 4		
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

Appropriate Technical Documentation and/or Specific Technical Documentation:

Appropriate Technical Documentation: No. 1


Performance without further testing: reaction to fire class E<sub>fi</sub>

Fulfilled requirements: Maximum layer thickness: 4 mm; Organic content: 100 % in weight

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Hans-Otto Munz  
Technical Manager



Hünxe, September, 10th 2019