

DECLARATION OF PERFORMANCE

**according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014**

No. LE_GI 710_V02

Unique identification code of the product-type:	GI 710
Intended use/es:	EN 1504-2 Surface protection products – Coating Protection against ingress (1.3) Moisture control (2.2) Increasing resistivity (8.2) EN 13813 Synthetic resin screed for internal uses
Manufacturer:	Gremmler Bauchemie GmbH Lise-Meitner-Strasse 5 46569 Hünxe
System/s of AVCP:	EN 1504-2: System 2+ (for uses in buildings and civil engineering works) EN 13813: System 4 (for internal uses)
Harmonised standard:	EN 1504-2:2004 EN 13813:2002
Notified body/ies:	Kiwa Polymer Institut, identification number 1119

Declared performance:

Table 1: Performance in system according to EN 1504-2

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Linear shrinkage	NPD	System 2+	EN 1504-2:2004
Coefficient of thermal expansion	NPD		
Cross cut	NPD		
Permeability to CO ₂	$s_D > 50 \text{ m}$		
Water vapour permeability	class III		
Capillary absorption and permeability to water	$w < 0.1 \text{ kg}/(\text{m}^2 \times \text{h}^{0.5})$		
Thermal compatibility	NPD		
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Crack bridging ability	NPD		
Adhesion strength by pull off test	$\geq 2.0 (1.5) \text{ N}/\text{mm}^2$		
Reaction to fire	class E		
Skid resistance	NPD		
Artificial weathering	NPD		
Antistatic behaviour	NPD		
Adhesion on wet concrete	NPD		
Release of dangerous substances	NPD		

Table 2: Performance according to EN 13813

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire ¹⁾	class E _{fl}	System 4	EN 13813:2002
Release of corrosive substances	SR		
Water permeability	NPD		
Wear resistance	AR 1		
Bond strength	B 1.5		
Impact resistance	IR 4		
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

Appropriate Technical Documentation and/or Specific Technical Documentation:

Appropriate Technical Documentation: No. 1


Performance without further testing: reaction to fire class E_{fl}

Fulfilled requirements: Maximum layer thickness: 4 mm; Organic content: 100 % in weight

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Hans-Otto Munz
Technical Manager



Hünxe, June, 29th 2026